

TITLE OF THE INVENTION

HEAT-DISSIPATION STRUCTURE OF PLASMA DISPLAY PANEL DEVICE

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

5 The invention relates to a structure for dissipating heat generated in a drive unit of a plasma display panel in a plasma display panel device.

10 The present application claims priority from Japanese Application No. 2000-182445, the disclosure of which is incorporated herein by reference for all purposes.

DESCRIPTION OF THE RELATED ART

15 In a plasma display panel (hereinafter referred to as "PDP"), a display image is generated by applying a predetermined voltage between electrodes, disposed to intersect with each other, to produce electrical discharge between the electrodes in a discharge space formed between two glass substrates.

20 The electrodes of the PDP have a high voltage of several hundred volts applied to them. A drive unit developing the high voltage to drive the PDP generates high heat. For this reason, the PDP device needs a heat-dissipation structure for dissipating the heat generated in the drive unit into the atmosphere.

Fig. 8 is a lateral sectional view showing a PDP device having a conventional heat-dissipation structure as explained above.

25 In Fig. 8, a PDP 1 is secured on a chassis 2 made of metal such as aluminum by an adhesive tape 3. On the back face of the chassis 2 (the reverse of the face on which the PDP 1 is mounted), a circuit

board 4 making up a drive circuit for driving the PDP 1 is installed and electrically connected to the PDP 1 through a flexible cable (not shown).

On the circuit board 4, a plurality of electronic components E1 and drive modules E2 which make up the drive circuit are mounted.

The PDP 1 and the circuit board 4 which are linked by the chassis 2 are housed in a casing made up of a side case C1, a rear case C2, a front panel FP for protecting the display surface of the PDP 1, and others.

In an upper portion of the rear case C2, an exhaust fan F is installed for exhausting air from the casing. Heat dissipation is performed such that the exhaust fan F is driven to dissipate the air inside the casing, which is heated by the heat generated from the electronic components E1 and drive modules E2 mounted on the circuit board 4, into the atmosphere.

In the conventional PDP device as explained above, however, the electronic components E1 and the drive modules E2 which generate heat are mounted on one face of the single circuit board 4, which results in a crowded arrangement of the electronic components E1 and the drive modules E2 on the circuit board 4 as illustrated in Fig. 9. Hence, the conventional PDP device has a problem in which a heat-dissipating path for creating an air flow for the heat dissipation produced by the exhaust fan F cannot be provided sufficiently between the electronic components E1 and between the drive modules E2.

SUMMARY OF THE INVENTION

The present invention has been made to solve the problem

associated with heat dissipation in the conventional plasma display panel as described above.

It is therefore an object of the present invention to provide a heat-dissipation structure capable of performing efficient heat
5 dissipation in a plasma display panel device.

To attain the above object, a heat-dissipation structure of a plasma display panel device including a plasma display panel and a drive circuit for driving the plasma display panel, according to a first aspect of the present invention, has the feature of including
10 a plurality of circuit boards and having electronic components, making up the drive circuit, mounted separately on the plurality of circuit boards.

With the heat-dissipation structure of the plasma display panel device of the first aspect, the electronic components making up the
15 drive circuit for the plasma display panel are mounted separately on the plurality of individual circuit boards. For this reason, it is possible to increase each space between the adjacent electronic components as compared with the case where the electronic components are mounted on a single circuit board.

According to the first aspect, therefore, the heat dissipating
20 path for creating an air flow in order to dissipate the heat, generated from the heat-generating electronic components, from the plasma display panel device into the atmosphere, can be provided sufficiently between the heat-generating electronic components,
25 resulting in efficient heat dissipation.

This allows the elimination of the conventional need for installing an exhaust fan for dissipating heat. If exhaust fans

are installed, it is possible to reduce the number of exhaust fans.

To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to a second aspect has, in addition to the configuration of the first aspect, the feature
5 that an electronic component with the heat-generating property out of the electronic components making up the drive circuit is mounted on a required circuit board out of the plurality of circuit boards.

With this structure, it is possible to place an exhaust hole, an exhaust fan or the like above the required circuit board on which
10 the electronic component with the heat-generating property is mounted for collective exhausting, which results in further efficiency in performing the heat dissipation.

To attain the aforementioned object, the heat-dissipation structure of the plasma display panel device according to a third
15 aspect has, in addition to the configuration of the second aspect, the feature that the required circuit board is supported by a metal-made build-up frame which is thermally-conductively installed on a metal-made casing of the plasma display panel device and is in contact with at least part of the electronic components with the
20 heat-generating property mounted on the required circuit board.

According to the heat dissipation structure of the plasma display panel device of the third aspect, in addition to the heat dissipation achieved by exhausting the heated air flowing between the electronic components with the heat-generating property mounted
25 on the required circuit board, the heat generated from the electronic components, with the heat-generating property, in contact with the metal-made build-up frame is transferred through the build-up frame

to the metal-made casing of the plasma display panel device and also dissipated from the metal-made casing, resulting in further efficiency in performing the heat dissipation.

5 To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to a fourth aspect has, in addition to the configuration of the third aspect, the feature that the electronic components having the heat-generating property are mounted separately on both faces of the required circuit board, and the electronic component mounted on one face of the required
10 circuit board are in contact with the build-up frame.

With this structure, it is possible to further increase a width of the heat dissipating path between the electronic components having the heat-generating property. In addition, the heat generated by the electronic components mounted on the one face of the circuit
15 board is passed through the build-up frame and dissipated from the metal-made casing of the plasma display panel device into the atmosphere, resulting in further efficiency in performing the heat dissipation.

To attain the aforementioned object, the heat-dissipation
20 structure of the plasma display panel according to a fifth aspect has, in addition to the configuration of the third aspect, the feature that the electronic component mounted on the one face of the required circuit board and being in contact with the build-up frame is a heat-generating module.

25 With this structure, electronic components having the heat-generating property are designed in modules, and the heat generated by the heat-generating module significantly exhibiting

heat-generating property is dissipated by means of transferring the heat to the metal-made casing of the plasma display panel device, as well as means of exhausting the heated air. This results in further efficiency in performing the heat dissipation.

5 To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to a sixth aspect has, in addition to the configuration of the second aspect, the feature that part of the electronic components with the heat-generating property out of the electronic components making up the drive circuit
10 is mounted on the required circuit board out of the plurality of circuit boards, and another electronic component with the heat-generating property is mounted on a circuit board out of the plurality of circuit boards other than the required circuit board while being in thermal-conductive contact with the metal-made casing
15 of the plasma display panel device.

According to the heat-dissipation structure of the plasma display panel device of the sixth aspect, the heat generated by the another electronic components with the heat-generating property mounted on the circuit board other than the required circuit board
20 is dissipated by means of transferring the heat to the metal-made casing of the plasma display panel device, as well as means of exhausting the heated air. This results in further efficiency in performing the heat dissipation.

Further, it is not required to mount the electronic components
25 having the heat-generating property on both faces of the single circuit board in order to make thermal-conductive contact between part of the electronic components having the heat-generating property

and the metal-made casing of the plasma display panel device. For this reason, it is possible to minimize an increase in depth dimension of the plasma display panel device due to the provision of the heat-dissipation structure.

5 To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to a seventh aspect has, in addition to the configuration of the sixth aspect, the feature that the another electronic component with the heat-generating property is thermal-conductively installed to the metal-made casing
10 of the plasma display panel device and is in contact with a metal-made build-up frame supporting the required circuit board.

With this structure, the heat produced by the another electronic component with the heat-generating property is transferred through the metal-made build-up frame supporting the required circuit board
15 to the metal-made casing of the plasma display device to be dissipated from the casing into the atmosphere.

To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to an eighth aspect has, in addition to the configuration of the sixth aspect, the feature
20 that the another electronic components with the heat-generating property are a heat-generating module.

With this structure, the electronic components having the heat-generating property are designated in modules, and the heat produced by the resulting heat-generating module significantly
25 exhibiting the heat-generating property is dissipated by means of transferring the heat to the metal-made casing of the plasma display panel device, as well as means of exhausting the heated air. This

results in further efficiency in performing the heat dissipation.

To attain the aforementioned object, a heat-dissipation structure of a plasma display panel including a plasma display panel and a drive circuit for driving the plasma display panel according to a ninth aspect of the present invention has the feature that electronic components making up the drive circuit are mounted separately on both faces of a circuit board.

With the heat dissipation structure of the plasma display panel device of the ninth aspect, since the electronic components making up the drive circuit for the plasma display panel are mounted separately on both faces of the circuit board, it is possible to increase each space between the electronic components arranged thereon as compared with the case where the electronic components are mounted on one of the faces of the circuit board.

According to the ninth aspect, therefore, it is permitted that a heat-dissipating path for making air flow in order to dissipate the heat produced by the heat-generating electronic component from the plasma display panel device into the atmosphere, is provided sufficiently between the heat-generating electronic components, resulting in efficiency in performing the heat dissipation. Further, since there is no need for providing the circuit boards in plural in order to mount the electronic components separately, it is possible to reduce depth dimension of the plasma display panel device.

To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to a tenth aspect has, in addition to the configuration of the ninth aspect, the feature that the circuit board having both the faces on which the electrode

components are separately mounted is supported by a metal-made build-up frame installed thermal-conductively to the metal-made casing of the plasma display panel device and being in contact with part of at least the electronic components with the heat-generating property out of the electronic components mounted on the circuit board.

According to the tenth aspect of the heat dissipation structure of the plasma display panel device, in addition to the heat dissipation achieved by exhausting the heated air flowing between the electronic components with the heat-generating property mounted on the circuit board, the heat generated by the electronic components with the heat-generating property which are in contact with the metal-made build-up frame, is transferred through the build-up frame to the metal-made casing of the plasma display panel device to be dissipated also from the metal-made casing, resulting in further efficiency in performing the heat dissipation.

To attain the aforementioned object, the heat-dissipation structure of the plasma display panel according to an eleventh aspect has, in addition to the configuration of the tenth aspect, the feature that the electronic component mounted on the circuit board while being in contact with the build-up frame is a heat-generating module.

With this structure, the electronic components having the heat-generating property are designed in modules, and the heat generated by the resulting heat-generating module significantly exhibiting the heat-generating property is dissipated by means of transferring the heat to the metal-made casing of the plasma display panel device, as well as means of exhausting the heated air. This

results in further efficiency in performing the heat dissipation.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a lateral sectional view illustrating a first example according to a preferred embodiment of the present invention.

5 Fig. 2 is a perspective view illustrating arrangement of electronic components mounted on one face of a circuit board in the first example.

Fig. 3 is a perspective view illustrating arrangement of electronic components mounted on the other face of the circuit board.

10 Fig. 4 is a lateral sectional view illustrating a second example according to the preferred embodiment of the present invention.

Fig. 5 is a perspective view illustrating arrangement of circuit boards in the second embodiment.

15 Fig. 6 is a lateral sectional view illustrating a third example according to the preferred embodiment of the present invention.

Fig. 7 is a lateral sectional view illustrating a fourth example according to a preferred embodiment of the present invention.

Fig. 8 is a lateral sectional view illustrating an example of the prior art.

20 Fig. 9 is a perspective view illustrating arrangement of electronic components mounted on a circuit board in the prior art.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Most preferred embodiment according to the present invention will be described hereinafter in detail with reference to the
25 accompanying drawings.

Fig. 1 is a lateral sectional view illustrating a first example according to the preferred embodiment of the present invention.

Referring to Fig. 1, in a plasma display panel device (hereinafter referred to as a "PDP device") 10, as in the case of the conventional PDP device of Fig. 8, a PDP 1 is secured on a chassis 2 by an adhesive tape 3. On the back face of the chassis 2 (the reverse of the face on which the PDP 1 is mounted), a circuit board 4 making up a drive circuit for driving the PDP 1 is installed and electrically connected to the PDP 1 through a flexible cable (not shown).

The PDP 1 and the circuit board 4 which are jointed by the chassis 2 are housed in a casing made up of a side case C1, a metal-made rear case C2', a front panel FP for protecting the display surface of the PDP 1, and others.

In the above configuration, the components equivalent to those used in DESCRIPTION OF THE RELATED ART are designated by the same reference numerals.

The circuit board 4 has mounted on its back face (the reverse of the face on which the PDP 1 is mounted) a electronic component E1' exhibiting a less heat-generating property out of electronic components which are one part of the electronic components E1 and drive modules E2 which together make up a drive circuit of the PDP.

On an inner wall face of the rear case C2' opposing the circuit board 4, a heat-dissipative chassis 11 formed of metal such as aluminum is fixed through a thermal conductor 12. A circuit board 13 is installed on and supported by the heat-dissipative chassis 11.

On the front face of the circuit board 13 opposing the circuit board 4, electronic components E1" significantly exhibiting the heat-generating property out of the electronic components are mounted.

Further, on the back face of the circuit board 13 opposing the rear case C2', high heat-generating modules E2' are mounted in such a way that the opposite face to the face mounted on the circuit board 13 is in close contact with the heat-dissipative chassis 11.

5 The rear case C2' includes an exhaust hole C2a at a portion situated above the heat-dissipative chassis 11.

With the PDP device 10, the circuit board 13 is placed in isolation from the circuit board 4. The electronic components E1" significantly exhibiting the heat-generating property out of the electronic components and the high heat-generating modules E2' are mounted on the circuit board 13. Better still, the electronic component E1" significantly exhibiting the heat-generating property and the high heat-generating module E2' are disposed separately on the front face and the back face of the circuit board 13.

10
15 For this reason, as is seen from Fig. 2 illustrating the arrangement of the electronic components E1" mounted on the front face of the heat-dissipating chassis 11 and Fig. 3 illustrating the arrangement of the high heat-generating modules E2' mounted on the back face, each of spaces between the electronic components E1" and
20 between the high exothermic modules E2' is set so as to be large. This allows sufficient heat-dissipating paths.

As a result of the contact of the high heat-generating module E2' with the heat-dissipative chassis 11, heat generated from the high heat-generating module E2' is transferred through the
25 heat-dissipative chassis 11 and the thermal conductor 12 to the metal-made rear case C2', and then is dissipated from the rear case C2' into the atmosphere.

As described hereinbefore, in the PDP device 10, the air heated by the heat generation of the electronic component E1" and the high heat-generating module E2' moves upward through the heat-dissipating paths formed between the electronic components E1" and between the modules E2', and then is exhausted from the exhaust hole C2a, provided in the upper portion of the rear case C2', to the outside of the casing. Moreover, the heat generated by the high heat-generating module E2' is transferred through the heat-dissipative chassis 11 and the thermal conductor 12 to the rear case C2' to be dissipated therefrom into the atmosphere. Thus, the heat dissipation from the inside of the casing is performed efficiently.

In consequence, the provision of the heat dissipation structure as described above eliminates the conventional need of installing an exhaust fan for forcibly exhausting the heated air inside a casing. If exhaust fans are installed, it is possible to reduce the number of exhaust fans.

Fig. 4 is a lateral sectional view illustrating a second example according to the embodiment of the present invention.

Similarly to the PDP device of the first example, in a PDP device 20 of the second example, a circuit board 13' independent of a circuit board 4 is supported by a heat-dissipative chassis 11' installed through a thermal conductor 12 to a rear case C2', and therefore, is disposed at a position opposing the circuit board 4. An electron component E1" with the heat-generating property is mounted on the front face of the circuit board 13' opposing the circuit board 4.

As is clear from Fig. 5, the circuit board 13' is formed with a notch 13a in the upper left corner in Fig. 5.

While a high heat-generating module E2' is secured to and has a back face in close contact with the heat-dissipative chassis 11', it is disposed in the notch 13a of the circuit board 13'. Further, the module E2' is mounted on a circuit board 15 such that a face thereof opposing the circuit board 4 faces the circuit board 15.

The remaining configuration of the PDP device 20 is approximately the same as that of the PDP device 10 in the first example, and the same reference numerals are used.

With the PDP device 20 in the second example as well, the electronic component E1" significantly exhibiting the heat-generating property out of the electronic components and the high heat-generating modules E2' are mounted on the circuit board 13' and the circuit board 15, which are provided in isolate from the circuit board 4. Hence, each of spaces between the electronic components E1" and between the high heat-generating property modules E2' is set so as to be large. This allows sufficient heat-dissipating paths, and allows heat generated from the high heat-generating module E2' to be transferred to the rear case C2' and dissipated therefrom, resulting in effective heat dissipation.

In addition, in the PDP device 20, the high heat-generating module E2' is mounted on the circuit board 15 provided independently of the circuit board 13', and disposed in the notch 13a formed in the circuit board 13'. This allows a minimizing of the increase in the depth dimension of the PDP device due to the provision of the foregoing heat-dissipation structure.

Fig. 6 is a lateral sectional view illustrating a third example according to the embodiment of the present invention.

A PDP device 30 in Fig. 6 does not include a circuit board corresponding to the circuit board 4 of the PDP device 10 in Fig. 1, and includes electronic components E1', E1'', E2' mounted separately on both the faces of a circuit board 13. The remaining
5 configuration is approximately the same as that of the PDP device 10 in Fig. 1, and the same reference numerals are used.

Fig. 7 is a lateral sectional view illustrating a fourth example according to the embodiment of the present invention.

A PDP device 40 in Fig. 7 does not include a circuit board
10 corresponding to the circuit board 4 of the PDP device 20 in Fig. 4, and includes electronic components E1', E1'' mounted separately on both the faces of a circuit board 13'. The remaining configuration is approximately the same as that of the PDP device 20 in Fig. 4, and the same reference numerals are used.

In both the PDP device 30 of the third example and the PDP device
15 40 of the fourth example, sufficient heat dissipating paths are provided between the electronic components by means of mounting the electronic components separately on both the faces of the circuit board, as in the cases of the first and second examples. Further,
20 the heat dissipation is efficiently performed by means of transferring heat to the rear case C2'.

Further, each of the PDP devices 30 and 40 has a smaller number of circuit boards as compared with that of the PDP devices of the first and second example, which reduces the depth dimension of the
25 PDP device.

The terms and description used herein are set forth by way of illustration only and are not meant as limitations. Those skilled

in the art will recognize that numerous variations are possible within the spirit and scope of the invention as defined in the following claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000